

# Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 17

LOCTITE MR 3863 known as Loctite 3863 2g De/Au

SDS No. : 290257 V003.0 Revision: 09.01.2023 printing date: 10.01.2023 Replaces version from: 23.11.2022

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

LOCTITE MR 3863 known as Loctite 3863 2g De/Au

**1.2. Relevant identified uses of the substance or mixture and uses advised against** Intended use: Coating

# **1.3. Details of the supplier of the safety data sheet** Henkel AG & Co. KGaA

Henkelstr. 67 40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDS info. Adhesive @henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

# **1.4. Emergency telephone number**

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classification (CLP):	
Flammable liquids 0	Category 2
H225 Highly flammable liquid and vapour.	
Acute toxicity 0	Category 4
H332 Harmful if inhaled.	
Route of Exposure: Inhalation	
Serious eye irritation 0	Category 2
H319 Causes serious eye irritation.	
Carcinogenicity	Category 2
H351 Suspected of causing cancer.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	
Acute hazards to the aquatic environment	Category 1
H400 Very toxic to aquatic life.	
Chronic hazards to the aquatic environment	Category 1
H410 Very toxic to aquatic life with long lasting effects.	

2.2. Label elements	
Label elements (CLP):	
Hazard pictogram:	
Contains	4-methylpentan-2-one
	methanol
Signal word:	Danger
Hazard statement:	<ul> <li>H225 Highly flammable liquid and vapour.</li> <li>H319 Causes serious eye irritation.</li> <li>H332 Harmful if inhaled.</li> <li>H336 May cause drowsiness or dizziness.</li> <li>H351 Suspected of causing cancer.</li> <li>H410 Very toxic to aquatic life with long lasting effects.</li> </ul>
Supplemental information	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statement: Prevention	<ul><li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li><li>P273 Avoid release to the environment.</li><li>P280 Wear protective gloves/protective clothing.</li><li>P261 Avoid breathing spray.</li></ul>
Precautionary statement: Response	P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P337+P313 If eye irritation persists: Get medical advice/attention.
Precautionary statement: Storage	P403+P235 Store in a well-ventilated place. Keep cool.

# 2.3. Other hazards

None if used properly.

Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration  $\geq$  the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

# **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

#### Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
EC Number REACH-Reg No.				
4-methylpentan-2-one 108-10-1 203-550-1 01-2119473980-30	50- < 75 %	Acute Tox. 4, Inhalation, H332 Carc. 2, H351 Flam. Liq. 2, H225 STOT SE 3, H336 Eye Irrit. 2, H319	inhalation:ATE = 11 mg/l;vapour	EU OEL
Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4 231-131-3 01-2119555669-21	25- < 50 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 10 M chronic = 10	EU OEL
methanol 67-56-1 200-659-6 01-2119433307-44	0,1- < 1 %	Flam. Liq. 2, H225 Acute Tox. 3, Inhalation, H331 Acute Tox. 3, Dermal, H311 Acute Tox. 3, Oral, H301 STOT SE 1, H370	STOT SE 1; H370; C >= 10 % STOT SE 2; H371; C 3 - < 10 % ====== oral:ATE = 300 mg/kg	EU OEL

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Rinse with running water and soap. Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

**4.2. Most important symptoms and effects, both acute and delayed** EYE: Irritation, conjunctivitis.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

Prolonged or repeated skin contact with silver and its salts may cause a blue-gray discoloration of the skin and mucous membranes that is irreversible (Argyria).

**4.3. Indication of any immediate medical attention and special treatment needed** See section: Description of first aid measures

# **SECTION 5: Firefighting measures**

**5.1. Extinguishing media Suitable extinguishing media:** Carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:** High pressure waterjet

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

#### **5.3.** Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

### Additional information:

In case of fire, keep containers cool with water spray.

# **SECTION 6: Accidental release measures**

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Ensure adequate ventilation. Wear protective equipment.

#### **6.2.** Environmental precautions

Do not empty into drains / surface water / ground water.

#### 6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal. Dispose of contaminated material as waste according to Section 13.

#### 6.4. Reference to other sections

See advice in section 8

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Use only in well-ventilated areas. Vapours should be extracted to avoid inhalation. Keep away from sources of ignition - no smoking. Avoid skin and eye contact. See advice in section 8

#### Hygiene measures:

Good industrial hygiene practices should be observed. Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated place. Keep away from heat and direct sunlight. Refer to Technical Data Sheet

**7.3. Specific end use(s)** Coating

# SECTION 8: Exposure controls/personal protection

# 8.1. Control parameters

# **Occupational Exposure Limits**

Valid for

Germany

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
4-Methylpentan-2-one 108-10-1 [4-METHYLPENTAN-2-ONE]	20	83	Time Weighted Average (TWA):	Indicative	ECTLV
4-Methylpentan-2-one 108-10-1 [4-METHYLPENTAN-2-ONE]	50	208	Short Term Exposure Limit (STEL):	Indicative	ECTLV
4-Methylpentan-2-one 108-10-1	20	83	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
4-Methylpentan-2-one 108-10-1			Skin designation:	Can be absorbed through the skin.	TRGS 900
4-Methylpentan-2-one 108-10-1			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
Silver 7440-22-4 [SILVER, METALLIC]		0,1	Time Weighted Average (TWA):	Indicative	ECTLV
Silver 7440-22-4			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Silver 7440-22-4		0,1	Exposure limit(s):	8	TRGS 900
Methanol 67-56-1 [METHANOL]	200	260	Time Weighted Average (TWA):	Indicative	ECTLV
Methanol 67-56-1			Skin designation:	Can be absorbed through the skin.	TRGS 900
Methanol 67-56-1			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Methanol 67-56-1	100	130	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900

# Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	e Value				Remarks
	•	Î.	mg/l	ppm	mg/kg	others	
4-methylpentan-2-one 108-10-1	aqua (freshwater)		0,6 mg/l				
4-methylpentan-2-one 108-10-1	aqua (marine water)		0,06 mg/l				
4-methylpentan-2-one 108-10-1	sediment (freshwater)				8,27 mg/kg		
4-methylpentan-2-one 108-10-1	sediment (marine water)				0,83 mg/kg		
4-methylpentan-2-one 108-10-1	Soil				1,3 mg/kg		
4-methylpentan-2-one 108-10-1	sewage treatment plant (STP)		27,5 mg/l				
4-methylpentan-2-one 108-10-1	aqua (intermittent releases)		1,5 mg/l				
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	aqua (freshwater)		0,00004 mg/l				
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	aqua (marine water)		0,00086 mg/l				
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	sewage treatment plant (STP)		0,025 mg/l				
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	sediment (freshwater)				438,13 mg/kg		
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	sediment (marine water)				438,13 mg/kg		
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	Air						no hazard identified
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	Soil				1,41 mg/kg		
methanol 67-56-1	aqua (freshwater)						no hazard identified
methanol 67-56-1	sediment (freshwater)						no hazard identified
methanol 67-56-1	aqua (marine water)						no hazard identified
methanol 67-56-1	Soil						no hazard identified
methanol 67-56-1	sewage treatment plant (STP)						no hazard identified
methanol 67-56-1	aqua (intermittent releases)						no hazard identified
methanol 67-56-1	sediment (marine water)						no hazard identified

# Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
4-methylpentan-2-one	Workers	Inhalation	Acute/short term	Time	208 mg/m3	
$108_{-}10_{-}1$	WORKERS	minaration	exposure -		200 mg/m5	
100 10 1			systemic effects			
4-methylpentan-2-one	Workers	Inhalation	Acute/short term		208 mg/m3	
108-10-1	W OIKers	initiation	exposure - local		200 mg/ms	
			effects			
4-methylpentan-2-one	Workers	Inhalation	Long term		83 mg/m3	
108-10-1	() officers	initiation	exposure -		oo mg mo	
			systemic effects			
4-methylpentan-2-one	Workers	Inhalation	Long term		83 mg/m3	
108-10-1			exposure - local		0	
			effects			
4-methylpentan-2-one	Workers	dermal	Long term		11,8 mg/kg	
108-10-1			exposure -			
			systemic effects			
4-methylpentan-2-one	General	Inhalation	Acute/short term		155,2 mg/m3	
108-10-1	population		exposure -			
			systemic effects			
4-methylpentan-2-one	General	Inhalation	Acute/short term		155,2 mg/m3	
108-10-1	population		exposure - local			
			effects			
4-methylpentan-2-one	General	Inhalation	Long term		14,7 mg/m3	
108-10-1	population		exposure -			
	G 1		systemic effects		115 1 2	
4-methylpentan-2-one	General	Inhalation	Long term		14,7 mg/m3	
108-10-1	population		exposure - local			
4 4 1 1 4 2	0 1	1 1	effects		4.0 /	
4-methylpentan-2-one	General	dermal	Long term		4,2 mg/kg	
108-10-1	population		exposure -			
4 mathylpantan 2 ana	Comorol	o	L on a torm		4.2 ma/ka	
108 10 1	nonulation	orai	exposure		4,2 mg/kg	
100-10-1	population		systemic effects			
Silver $\geq -99.9\%$ Ag as powder	Workers	inhalation	Long term		$0.1 \text{ mg/m}^3$	no hazard identified
(>100nm<1mm) classified for environment	WORKERS	minalation	exposure -		0,1 mg/m5	no nazaru identified
7440-22-4			systemic effects			
Silver $\geq 99.9$ % Ag as powder	General	inhalation	Long term		0.04  mg/m3	no hazard identified
(>100nm<1mm) classified for environment	population	minuteron	exposure -		0,01 119 115	no nazaru identified
7440-22-4	r •r •····		systemic effects			
Silver $\geq 99.9$ % Ag as powder	General	oral	Long term		1,2 mg/kg	no hazard identified
(>100nm<1mm) classified for environment	population		exposure -			
7440-22-4	* *		systemic effects			
methanol	Workers	inhalation	Long term		260 mg/m3	no hazard identified
67-56-1			exposure -			
			systemic effects			
methanol	Workers	inhalation	Acute/short term		260 mg/m3	no hazard identified
67-56-1			exposure -			
			systemic effects			
methanol	Workers	inhalation	Long term		260 mg/m3	no hazard identified
67-56-1			exposure - local			
			effects		0.00	
methanol	Workers	inhalation	Acute/short term		260 mg/m3	no hazard identified
67-56-1			exposure - local			
	<b>W</b> 1		Lawater		40	and the second idea of the d
	workers	dermal	Long term		40 mg/kg	no nazard identified
07-30-1			exposure -			
methanol	Workers	dermal	Acute/short term		40 mg/kg	no hazard identified
67-56-1	WORKERS	dermai	exposure -		40 mg/kg	no nazaru identified
07 50 1			systemic effects			
methanol	General	inhalation	Long term		50 mg/m3	no hazard identified
67-56-1	population		exposure -		e o mg me	no nazaro nooninteo
	r · r · · · ·		systemic effects			
methanol	General	inhalation	Acute/short term		50 mg/m3	no hazard identified
67-56-1	population		exposure -		-	
	-		systemic effects			
methanol	General	inhalation	Long term		50 mg/m3	no hazard identified
67-56-1	population		exposure - local			
			effects			
methanol	General	inhalation	Acute/short term		50 mg/m3	no hazard identified
67-56-1	population		exposure - local			

			effects		
methanol 67-56-1	General population	dermal	Long term exposure - systemic effects	8 mg/kg	no hazard identified
methanol 67-56-1	General population	dermal	Acute/short term exposure - systemic effects	8 mg/kg	no hazard identified
methanol 67-56-1	General population	oral	Long term exposure - systemic effects	8 mg/kg	no hazard identified
methanol 67-56-1	General population	oral	Acute/short term exposure - systemic effects	8 mg/kg	no hazard identified

#### **Biological Exposure Indices:**

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
4-Methylpentan-2-one 108-10-1	4- methylpentan -2-one	Urine	Sampling time: End of shift.	3,5 mg/l	DE BAT		
4-Methylpentan-2-one 108-10-1	4- methylpentan -2-one	Urine	Sampling time: End of shift.	0,7 mg/l	DE BGW		
Methanol 67-56-1 [METHANOL]	methanol	Urine	Sampling time period is for long-term exposures, at the end of the shift after several preceding ones./ Sampling time period is at end of exposure or at end of shift.	15 mg/l	DE BGW		

### 8.2. Exposure controls:

Engineering controls: Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state	liquid
Delivery form	Currently under determination
Colour	silver
Odor	characteristic
Melting point	Not available.
Initial boiling point	114 °C (237.2 °F)
Flammability	The product is not flammable.
Explosive limits	Not applicable, The product is not flammable.
Flash point	14 °C (57.2 °F)
Auto-ignition temperature	485 °C (905 °F)
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no
	organic peroxide and does not decompose under foreseen
	conditions of use
pH	Not available.
Viscosity (kinematic)	> 20,5 mm2/s
(40 °C (104 °F); )	
Solubility (qualitative)	Not miscible
(20 °C (68 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
	Mixture
Vapour pressure	8 hPa
(20 °C (68 °F))	
Density	0,96 g/cm3 None
(20 °C (68 °F))	
Relative vapour density:	1
(20 °C)	
Particle characteristics	Not applicable
	Product is a liquid
Other information	

Other information not applicable for this product

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

Reaction with strong acids. Reacts with strong oxidants.

#### **10.2. Chemical stability** Stable under recommended storage conditions.

## 10.3. Possibility of hazardous reactions

See section reactivity

#### **10.4.** Conditions to avoid

No decomposition if used according to specifications.

#### **10.5. Incompatible materials**

See section reactivity.

#### 10.6. Hazardous decomposition products

None if used for intended purpose.

# **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

# Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
4-methylpentan-2-one	LD50	2.080 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral
108-10-1				Toxicity)
Silver >= 99,9 % Ag in	LD50	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
powder (>100nm<1mm)				
7440-22-4				
methanol	Acute	300 mg/kg		Expert judgement
67-56-1	toxicity			
	estimate			
	(ATE)			

#### Acute dermal toxicity:

Prolonged or repeated skin contact with silver and its salts may cause a blue-gray discoloration of the skin and mucous membranes that is irreversible (Argyria).

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
4-methylpentan-2-one	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
108-10-1				
4-methylpentan-2-one	LD0	>= 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
108-10-1				
Silver >= 99,9 % Ag in	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
powder (>100nm<1mm)				
7440-22-4				

#### Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
4-methylpentan-2-one 108-10-1	Acute toxicity estimate (ATE)	11 mg/l	vapour			Expert judgement
4-methylpentan-2-one 108-10-1	LC50	8,2 - 16,4 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)

#### Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
4-methylpentan-2-one 108-10-1	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
methanol 67-56-1	not irritating	20 h	rabbit	BASF Test

# Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
4-methylpentan-2-one	slightly		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
108-10-1	irritating			
methanol	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
67-56-1				

# Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
4-methylpentan-2-one 108-10-1	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
methanol 67-56-1	not sensitising	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)

# Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Type of study /	Metabolic	Species	Method
CAS-No.		Route of administration	activation /		
4-methylpentan-2-one 108-10-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
4-methylpentan-2-one 108-10-1	negative	in vitro mammalian chromosome aberration test	without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
4-methylpentan-2-one 108-10-1	ambiguous without metabolic activation	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
methanol 67-56-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
methanol 67-56-1	negative	in vitro mammalian cell micronucleus test	without		not specified
methanol 67-56-1	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
4-methylpentan-2-one 108-10-1	negative	intraperitoneal		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
methanol 67-56-1	negative	intraperitoneal		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

# Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components	Result	Route of	Exposure	Species	Sex	Method
CAS-No.		application	time /			
			Frequency			
			of treatment			
4-methylpentan-2-one		inhalation:	2 y	rat	male/female	OECD Guideline 451
108-10-1		vapour	6 h/d, 5 d/w			(Carcinogenicity
						Studies)
methanol	not carcinogenic	inhalation:	18 m	mouse	male/female	equivalent or similar
67-56-1		vapour	19 h/d			OECD Guideline 453
						(Combined Chronic
						Toxicity /
						Carcinogenicity
						Studies)

# **Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
4-methylpentan-2-one		screening	oral: gavage	rat	OECD Guideline 422
108-10-1					(Combined Repeated Dose
					Toxicity Study with the
					Reproduction /
					Developmental Toxicity
					Screening Test)
4-methylpentan-2-one		One	oral: gavage	rat	OECD Guideline 415 (One-
108-10-1		generation			Generation Reproduction
		study			Toxicity Study)
4-methylpentan-2-one		Two	oral: gavage	rat	OECD Guideline 416 (Two-
108-10-1		generation			Generation Reproduction
		study			Toxicity Study)
methanol	NOAEL P 1,3 mg/l	Two	inhalation	rat	equivalent or similar to
67-56-1		generation			OECD Guideline 416 (Two-
	NOAEL F1 0,13 mg/l	study			Generation Reproduction
					Toxicity Study)
	NOAEL F2 0,13 mg/l				

# STOT-single exposure:

No data available.

# STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
4-methylpentan-2-one 108-10-1	NOAEL 250 mg/kg	oral: gavage	13 w daily	rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
methanol 67-56-1	NOAEL 6,63 mg/l	inhalation: vapour	4 weeks 6 h/d, 5 d/w	rat	equivalent or similar to OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day)
methanol 67-56-1	NOAEL 0,13 mg/l	inhalation: vapour	12 m 20 h/d	rat	equivalent or similar to OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

#### Aspiration hazard:

No data available.

### 11.2 Information on other hazards

not applicable

# **SECTION 12: Ecological information**

# General ecological information:

Do not empty into drains / surface water / ground water.

#### 12.1. Toxicity

# Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
4-methylpentan-2-one	LC50	600 mg/l	96 h	Salmo gairdneri (new name:	OECD Guideline 203 (Fish,
108-10-1				Oncorhynchus mykiss)	Acute Toxicity Test)
Silver >= 99,9 % Ag in	LC50	0,0012 mg/l	96 h	Pimephales promelas	other guideline:
powder (>100nm<1mm)					
7440-22-4					
Silver >= 99,9 % Ag in	EC10	0,00019 mg/l	217 d	Salmo trutta	OECD Guideline 210 (fish
powder (>100nm<1mm)					early lite stage toxicity test)
7440-22-4					
methanol	LC50	15.400 mg/l	96 h	Lepomis macrochirus	EPA-660 (Methods for
67-56-1					Acute Toxicity Tests with
					Fish, Macroinvertebrates
					and Amphibians)
methanol	NOEC	7.900 mg/l	200 h	Oryzias latipes	OECD Guideline 210 (fish
67-56-1					early lite stage toxicity test)

# Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
4-methylpentan-2-one 108-10-1	EC50	170 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4	EC50	0,00022 mg/l	48 h	Daphnia magna	other guideline:
methanol 67-56-1	EC50	18.260 mg/l	96 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

#### Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_		
Silver >= 99,9 % Ag in	NOEC	0,00032 mg/l	21 d	Daphnia magna	EPA OPPTS 850.1300
powder (>100nm<1mm)					(Daphnid Chronic Toxicity
7440-22-4					Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
4-methylpentan-2-one	EC50	400 mg/l	96 h	Selenastrum capricornutum	OECD Guideline 201 (Alga,
108-10-1				(new name: Pseudokirchneriella	Growth Inhibition Test)
				subcapitata)	
Silver >= 99,9 % Ag in	EC10	0,00016 mg/l	15 d	other:	other guideline:
powder (>100nm<1mm)					
7440-22-4					
methanol	EC50	22.000 mg/l	96 h	Selenastrum capricornutum	OECD Guideline 201 (Alga,
67-56-1		-		(new name: Pseudokirchneriella	Growth Inhibition Test)
				subcapitata)	

### Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
4-methylpentan-2-one 108-10-1	EC0	275 mg/l	16 h		not specified
methanol 67-56-1	IC50	> 1.000 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

# 12.2. Persistence and degradability

No data available.

Hazardous substances	Result	Test type	Degradability	Exposure	Method
CAS-No.				time	
4-methylpentan-2-one	readily biodegradable	aerobic	99 %	7 day	OECD Guideline 301 E (Ready
108-10-1					biodegradability: Modified OECD
					Screening Test)
methanol	readily biodegradable	aerobic	82 - 92 %	30 d	EU Method C.4-E (Determination
67-56-1					of the "Ready"
					BiodegradabilityClosed Bottle
					Test)

# **12.3.** Bioaccumulative potential

No data available.

Hazardous substances	Bioconcentratio	Exposure time	Temperature	Species	Method
CAS-No.	n factor (BCF)				
Silver >= 99,9 % Ag in	70	42 d	20 °C	Cyprinus carpio	other guideline:
powder (>100nm<1mm)					
7440-22-4					
methanol	< 10	72 h		Leuciscus idus	not specified
67-56-1				melanotus	

# 12.4. Mobility in soil

The product is insoluble and floats on water.

Hazardous substances	LogPow	Temperature	Method
CAS-No.			
4-methylpentan-2-one	1,31	20 °C	not specified
108-10-1			
methanol	-0,77		other guideline:
67-56-1			

# 12.5. Results of PBT and vPvB assessment

Hazardous substances	PBT / vPvB
CAS-No.	
4-methylpentan-2-one	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
108-10-1	Bioaccumulative (vPvB) criteria.
Silver >= 99,9 % Ag in powder (>100nm<1mm	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
)	Bioaccumulative (vPvB) criteria.
7440-22-4	
methanol	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
67-56-1	Bioaccumulative (vPvB) criteria.

#### 12.6. Endocrine disrupting properties

not applicable

### 12.7. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product disposal: Dispose of in accordance with local and national regulations. Collection and delivery to recycling enterprise or other registered elimination institution.

#### Disposal of uncleaned packages:

Disposal must be made according to official regulations.

Waste code

14 06 03 - other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

# Page 16 of 17

# **SECTION 14: Transport information**

#### 14.1. UN number or ID number

1.00	10.00
ADR	1263
RID	1263
ADN	1263
IMDG	1263
IATA	1263

#### 14.2. UN proper shipping name

ADR	PAINT RELATED MATERIAL
RID	PAINT RELATED MATERIAL
ADN	PAINT RELATED MATERIAL
IMDG	PAINT RELATED MATERIAL (Silver)
IATA	Paint related material

#### Transport hazard class(es) 14.3.

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

#### 14.4. Packing group

II
II
II
II
II

#### 14.5. **Environmental hazards**

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine pollutant
IATA	not applicable

#### 14.6. Special precautions for user

ADR	Special provision 640D
	Tunnelcode: (D/E)
RID	Special provision 640D
ADN	Special provision 640D
IMDG	not applicable
IATA	not applicable

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Persistent organic pollutants (Regulation (EU) 2019/1021):

Not applicable Not applicable Not applicable

VOC content (2010/75/EC)

#### **15.2.** Chemical safety assessment

A chemical safety assessment has not been carried out.

#### National regulations/information (Germany):

WGK:WGK 3: highly hazardous to water (Ordinance on facilities for handling<br/>substances that are hazardous to water (AwSV) )<br/>Classification according to AwSV, Annex 1 (5.2)

Storage class according to TRGS 510:

# **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

3

- H225 Highly flammable liquid and vapour.
- H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H370 Causes damage to organs.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very
	bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

#### Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.